

### **Greased Lightning**



### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product identifier:** Greased Lightning

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Cleaner. For professional users/industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Quill International Chemicals Ltd

Castle Lane

DE73 8JB Derby - Melbourne - United Kingdom

Phone: 01332694060

chemsales@quillinternational.com

1.4 Emergency telephone number: 01332 864664 (Mon - Fri 08:00 - 17:00 UK Time). For medical advice contact your GP or

NHS 111.

#### **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture:

#### **GB CLP Regulation:**

Classification of this product has been carried out in accordance with GB CLP Regulation.

Eye Dam. 1: Serious eye damage, Category 1, H318

Skin Corr. 1: Skin corrosion, Category 1, H314

#### 2.2 Label elements:

#### **GB CLP Regulation:**

Danger



### **Hazard statements:**

Skin Corr. 1: H314 - Causes severe skin burns and eye damage.

### **Precautionary statements:**

P280: Wear protective gloves/protective clothing/eye protection/protective footwear.

P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P310: Immediately call a POISON CENTER/doctor.

### Substances that contribute to the classification

Alcohol ethoxylated (C9-C11) (6 EO) (CAS: 68439-46-3); Disodium metasilicate 5 H2O (CAS: 10213-79-3); sodium hydroxide (CAS: 1310-73-2)

#### 2.3 Other hazards:

Product does not meet PBT/vPvB criteria

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substance:

Non-applicable

### 3.2 Mixture:

Chemical description: Mixture of substances

Components:

Date of compilation: 03/02/2022

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

Version: 7 (Replaced 6)

Revised: 13/11/2023

Page 1/12



### **Greased Lightning**



### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

	Identification	Chemical name/Classification	Concentration
CAS:	68439-46-3	Alcohol ethoxylated (C9-C11) (6 EO) Acute Tox. 4: H302; Eye Dam. 1: H318 - Danger	1 - <10 %
CAS:	10213-79-3	Disodium metasilicate · 5 H2O Skin Corr. 1B: H314; STOT SE 3: H335 - Danger	1 - <10 %
CAS:	111-76-2	2-butoxyethanol Acute Tox. 3: H331; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Danger	1 - <10 %
CAS:	13235-36-4	Ethylenediaminetetraacetic acid tetrasodium salt tetrahydrate  Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning	1 - <10 %
CAS:	1310-73-2	sodium hydroxide Skin Corr. 1A: H314 - Danger	1 - <10 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		
2-butoxyethanol	LD50 oral	1200 mg/kg (ATEi)	Rat
CAS: 111-76-2	LD50 dermal	Non-applicable	
	LC50 inhalation	3 mg/L (ATEi)	
Ethylenediaminetetraacetic acid tetrasodium salt tetrahydrate	LD50 oral	500 mg/kg (ATEi)	
CAS: 13235-36-4	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
Alcohol ethoxylated (C9-C11) (6 EO)	LD50 oral	500 mg/kg (ATEi)	
CAS: 68439-46-3	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	

### **SECTION 4: FIRST AID MEASURES**

#### 4.1 **Description of first aid measures:**

Request medical assistance immediately, showing the SDS of this product.

#### By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

### By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and also risk damage to the respiratory system through inhalation. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

#### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable



### **Greased Lightning**



#### **SECTION 5: FIREFIGHTING MEASURES**

### 5.1 Extinguishing media:

#### Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

#### Unsuitable extinguishing media:

Non-applicable

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

#### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

#### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

#### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.

#### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

#### 7.2 Conditions for safe storage, including any incompatibilities:

Date of compilation: 03/02/2022 Revised: 13/11/2023 Version: 7 (Replaced 6) Page 3/12



# **Greased Lightning**



### SECTION 7: HANDLING AND STORAGE (continued)

A.- Technical measures for storage

Minimum Temp.: 0 °C

Maximum Temp.: 40 °C

Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

#### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Elito 2005 Workplace exposure limited fourtif edition, published 20201						
Identification	Occupational exposure limits		nits			
2-butoxyethanol	WEL (8h)	25 ppm	123 mg/m <sup>3</sup>			
CAS: 111-76-2	WEL (15 min)	50 ppm	246 mg/m <sup>3</sup>			
sodium hydroxide	WEL (8h)					
CAS: 1310-73-2	WEL (15 min)		2 mg/m <sup>3</sup>			

#### **Biological limit values:**

BIOLOGICAL MONITORING GUIDANCE VALUES (BMGVS) - EH40/2005

Identification	NULL	NULL	NULL
2-butoxyethanol CAS: 111-76-2	280 mg/g (NULL)	Butoxyacetic acid in urine	Post shift

### **DNEL (Workers):**

		Short e	xposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Disodium metasilicate 5 H2O	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 10213-79-3	Dermal	Non-applicable	Non-applicable	1.49 mg/kg	Non-applicable
EC: 600-279-4	Inhalation	Non-applicable	Non-applicable	6.22 mg/m <sup>3</sup>	Non-applicable
2-butoxyethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	125 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	1091 mg/m <sup>3</sup>	246 mg/m <sup>3</sup>	98 mg/m <sup>3</sup>	Non-applicable
sodium hydroxide	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1310-73-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 215-185-5	Inhalation	Non-applicable	Non-applicable	Non-applicable	1 mg/m³

### **DNEL (General population):**

		Short e	xposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Disodium metasilicate <sup>-</sup> 5 H2O	Oral	Non-applicable	Non-applicable	0.74 mg/kg	Non-applicable
CAS: 10213-79-3	Dermal	Non-applicable	Non-applicable	0.74 mg/kg	Non-applicable
EC: 600-279-4	Inhalation	Non-applicable	Non-applicable	1.55 mg/m <sup>3</sup>	Non-applicable
2-butoxyethanol	Oral	Non-applicable	Non-applicable	6.3 mg/kg	Non-applicable
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	426 mg/m <sup>3</sup>	147 mg/m <sup>3</sup>	59 mg/m <sup>3</sup>	Non-applicable
sodium hydroxide	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1310-73-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 215-185-5	Inhalation	Non-applicable	Non-applicable	Non-applicable	1 mg/m³

PNEC:

Date of compilation: 03/02/2022 Revised: 13/11/2023 Version: 7 (Replaced 6) Page 4/12



### **Greased Lightning**



### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification						
Disodium metasilicate 5 H2O	STP	1000 mg/L	Fresh water	7.5 mg/L		
CAS: 10213-79-3	Soil	Non-applicable	Marine water	1 mg/L		
EC: 600-279-4	Intermittent	7.5 mg/L	Sediment (Fresh water)	Non-applicable		
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable		
2-butoxyethanol	STP	463 mg/L	Fresh water	8.8 mg/L		
CAS: 111-76-2	Soil	2.33 mg/kg	Marine water	0.88 mg/L		
EC: 203-905-0	Intermittent	26.4 mg/L	Sediment (Fresh water)	34.6 mg/kg		
	Oral	0.02 g/kg	Sediment (Marine water)	3.46 mg/kg		

### 8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding << UKCA marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.11 mm)	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

#### D.- Eye and face protection

Pictogram	PPE	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions.  Use if there is a risk of splashing.

### E.- Body protection

Pictogram	PPE	Remarks
	Work clothing	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

### F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
+	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	<b>→</b>	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

### **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:



### **Greased Lightning**



### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

V.O.C. (Supply): 8.65 % weight V.O.C. density at 20  $^{\circ}$ C: 90 kg/m³ (90 g/L)

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid

Appearance: Not available

Colour: Prussian blue

Odour: Citric

Odour threshold: Non-applicable \*

Volatility:

Boiling point at atmospheric pressure: 104 °C Vapour pressure at 20 °C: 2322 Pa

Vapour pressure at 50 °C: 12233.03 Pa (12.23 kPa)

Evaporation rate at 20 °C: Non-applicable \*

**Product description:** 

Density at 20 °C: 1040.7 kg/m<sup>3</sup>

Relative density at 20 °C: 1.041

Dynamic viscosity at 20 °C:

Kinematic viscosity at 20 °C:

Kinematic viscosity at 40 °C:

Non-applicable \*

Non-applicable \*

Non-applicable \*

Non-applicable \*

pH: 14

Vapour density at 20 °C:

Partition coefficient n-octanol/water 20 °C:

Solubility in water at 20 °C:

Non-applicable \*

Non-applicable \*

Non-applicable \*

Non-applicable \*

Non-applicable \*

Melting point/freezing point:

Non-applicable \*

Flammability:

Flash Point: 74 °C

Flammability (solid, gas):

Autoignition temperature:

Non-applicable \*

225 °C

Lower flammability limit: Non-applicable \* Upper flammability limit: Non-applicable \*

**Particle characteristics:** 

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Non-applicable \*
Oxidising properties: Non-applicable \*
Corrosive to metals: Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

Date of compilation: 03/02/2022 Revised: 13/11/2023 Version: 7 (Replaced 6) Page 6/12



### **Greased Lightning**



### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Heat of combustion: Non-applicable \*
Aerosols-total percentage (by mass) of flammable Non-applicable \*

components:

Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

Non-applicable \*

Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

#### SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

#### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

#### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Precaution	Not applicable	Not applicable

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

#### **Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
  - Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.
- B- Inhalation (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
  - Contact with the eyes: Produces serious eye damage after contact.

Date of compilation: 03/02/2022 Revised: 13/11/2023 Version: 7 (Replaced 6) Page 7/12



### **Greased Lightning**



#### SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
    - IARC: 2-butoxyethanol (3); (r)-p-mentha-1,8-diene (3); 7-methyl-3-methyleneocta-1,6-diene (2B)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### Other information:

Non-applicable

### Specific toxicology information on the substances:

Identification	Ac	Acute toxicity		
2-butoxyethanol	LD50 oral	1200 mg/kg (ATEi)	Rat	
CAS: 111-76-2	LD50 dermal	3000 mg/kg	Rabbit	
	LC50 inhalation	3 mg/L (ATEi)		
Ethylenediaminetetraacetic acid tetrasodium salt tetrahydrate	LD50 oral	500 mg/kg (ATEi)		
CAS: 13235-36-4	LD50 dermal	Non-applicable		
	LC50 inhalation	Non-applicable		
Alcohol ethoxylated (C9-C11) (6 EO)	LD50 oral	500 mg/kg (ATEi)		
CAS: 68439-46-3	LD50 dermal	Non-applicable		
	LC50 inhalation	Non-applicable		

### SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### 12.1 Toxicity:

#### Acute toxicity:

noute textery!					
Identification		Concentration	Species	Genus	
Alcohol ethoxylated (C9-C11) (6 EO)	LC50	6 mg/L (96 h)	N/A	Fish	
CAS: 68439-46-3	EC50	5.3 mg/L (48 h)	N/A	Crustacean	
	EC50	Non-applicable			
Disodium metasilicate · 5 H2O	LC50	210 mg/L (96 h)	Brachydanio rerio	Fish	
CAS: 10213-79-3	EC50	216 mg/L (96 h)	Daphnia magna	Crustacean	
	EC50	Non-applicable			

Date of compilation: 03/02/2022 Revised: 13/11/2023 Version: 7 (Replaced 6) **Page 8/12** 



### **Greased Lightning**



### SECTION 12: ECOLOGICAL INFORMATION (continued)

Identi	fication	Concentration		Species	Genus
2-butoxyethanol		LC50 1490 mg/L (96 h)		Lepomis macrochirus	Fish
CAS: 111-76-2		EC50	1815 mg/L (48 h)	Daphnia magna	Crustacean
		EC50	911 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
sodium hydroxide		LC50	189 mg/L (48 h)	Leuciscus idus	Fish
CAS: 1310-73-2		EC50	33 mg/L	Crangon crangon	Crustacean
		EC50	Non-applicable		

#### **Chronic toxicity:**

Identification	Concentration		Species	Genus
2-butoxyethanol		100 mg/L	Danio rerio	Fish
CAS: 111-76-2	NOEC	100 mg/L	Daphnia magna	Crustacean

### 12.2 Persistence and degradability:

### **Substance-specific information:**

Identification	Degradability		Biodegradability	
Alcohol ethoxylated (C9-C11) (6 EO)	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 68439-46-3	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	60 %
2-butoxyethanol	BOD5	0.71 g O2/g	Concentration	100 mg/L
CAS: 111-76-2	COD	2.2 g O2/g	Period	14 days
	BOD5/COD	0.32	% Biodegradable	96 %

#### 12.3 Bioaccumulative potential:

#### **Substance-specific information:**

Identification	Bioaccumulation potential		
2-butoxyethanol	BCF	3	
CAS: 111-76-2	Pow Log	0.83	
	Potential	Low	

# 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
2-butoxyethanol	Koc	8	Henry	1.621E-1 Pa·m³/mol
CAS: 111-76-2	Conclusion	Very High	Dry soil	No
	Surface tension	2.729E-2 N/m (25 °C)	Moist soil	Yes

### 12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

### 12.6 Other adverse effects:

Not described

### SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods:

Code	Description	Waste class
20 01 2	detergents containing hazardous substances	Dangerous

#### Type of waste:

**HP8** Corrosive

### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

### Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:



### **Greased Lightning**



### SECTION 13: DISPOSAL CONSIDERATIONS (continued)

UK legislation: The Waste Regulations 2011.

### **SECTION 14: TRANSPORT INFORMATION**

#### Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



14.1 UN number: UN3267

14.2 UN proper shipping name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Disodium

metasilicate 5 H2O)

14.3 Transport hazard class(es): Labels:

14.4 Packing group: ΙΙ 14.5 Environmental hazards: No 14.6 Special precautions for user

> Tunnel restriction code: Ε

Physico-Chemical properties: see section 9

Limited quantities: 1 L

14.7 Transport in bulk according

to Annex II of Marpol and the IBC Code:

Non-applicable

### Transport of dangerous goods by sea:

With regard to IMDG 40-20:

UN3267 14.1 UN number:

14.2 UN proper shipping name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Disodium

metasilicate 5 H2O)

14.3 Transport hazard class(es):

Labels: 8 14.4 Packing group: ΙΙ 14.5 Marine pollutant: No

14.6 Special precautions for user

Special regulations: 274 EmS Codes: F-A, S-B Physico-Chemical properties: see section 9

Limited quantities: 1 L SGG18 Segregation group:

14.7 Transport in bulk according

to Annex II of Marpol and the IBC Code:

Non-applicable

### Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:



14.1 UN number:

14.2 UN proper shipping name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Disodium

metasilicate 5 H2O)

14.3 Transport hazard class(es):

Labels: 8 14.4 Packing group: II

14.6 Special precautions for user

14.5 Environmental hazards:

Physico-Chemical properties: see section 9 Non-applicable

14.7 Transport in bulk according to Annex II of Marpol and

the IBC Code:

- CONTINUED ON NEXT PAGE -

No

Version: 7 (Replaced 6) Date of compilation: 03/02/2022 Revised: 13/11/2023 Page 10/12



### **Greased Lightning**



#### **SECTION 15: REGULATORY INFORMATION**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Non-applicable
- Substances listed in UK REACH Authorisation List (Annex 14): Non-applicable

#### The Detergents (Amendment) (EU Exit) Regulations:

In accordance with this regulation the product complies with the following:

The tensoactives contained in this mixture comply with the biodegradibility criteria stipulated in The Detergents (Amendment) (EU Exit) Regulations. The information to prove this is available to the relevant authorities of the Member States and will be shown to them by direct request or the request of a detergent manufacturer.

#### Labelling for contents:

Component	Concentration interval
EDTA and salts thereof	% (w/w) < 5
Amphoteric surfactants	% (w/w) < 5
Non-ionic surfactants	% (w/w) < 5
perfumes	

#### The Control of Major Accident Hazards Regulations 2015:

Non-applicable

# Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc ....):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- —tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

#### Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

COSHH-SR24 Storing chemical products (small scale).

COSHH-SR2 Diluting chemical concentrates.

COSHH-SR4 Manual cleaning and disinfecting surfaces.

The Product Safety and Metrology etc. (Amendment etc.) (EU Exit) Regulations 2019: SCHEDULE 34 - Amendment of Regulation (EC) No 1223/2009 and related amendments.

The Detergents (Amendment) (EU Exit) Regulations 2020.

# SECTION 16: OTHER INFORMATION

### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

### Texts of the legislative phrases mentioned in section 2:

H318: Causes serious eye damage.

H314: Causes severe skin burns and eye damage.

### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation:



### **Greased Lightning**



### SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 3: H331 - Toxic if inhaled. Acute Tox. 4: H302 - Harmful if swallowed. Eye Dam. 1: H318 - Causes serious eye damage. Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Corr. 1A: H314 - Causes severe skin burns and eye damage. Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT SE 3: H335 - May cause respiratory irritation.

### Classification procedure:

Eye Dam. 1: Calculation method Skin Corr. 1: Calculation method Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

#### Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET 
Date of compilation: 03/02/2022 Revised: 13/11/2023 Version: 7 (Replaced 6) Page 12/12